

CAM-264

16 POE PORTS 10/100M SWITCH (CCTV MODE UP TO 250M) + 2 GIGA UPLINK PORTS



FEATURES

- Transmission up to 250 meters
- VLAN supported
- PoE power supply up to 30W per port
- Automatic connected device detection
- 2x Uplink Gigabit
- Great quality/price
- Use UTP CAT5 cable or superior
- Unmanageable switch (L2)

PORT DESCRIPTION

PoE ports	16x RJ45 10/100M autonegociated
Uplink ports	16x RJ45 10/100M + 2x RJ45 10/100/1000M autonegociated

POE POWER SUPPLY

PoE max output	30W
Total consumption	150W
PoE port priority	Supported

GENERAL

Processing type	store and forward
Transmission model	IEEE802.3X full-duplex / Backpressure half-duplex
Backplane bandwidth	7,2Gbps
Package transference rate	5,36Mpps
MAC address	4K
Standard	IEEE802.3i 10 BASE-T, IEEE802.3u 100 BASE-TX, IEEE802.3ab 1000 BASE-T, IEEE802.3x flux control, IEEE802.3af (PoE), IEEE802.3at (PoE+), IEEE802.3az EEE

ELECTRICAL & ENVIRONMENTAL

Power supply	100V ~ 240V AC, 50/60Hz
Working temperature	-10°C ~ +45°C, 10% ~ 90% RH

PHYSICAL FEATURES

Dimensions	282 x 178 x 44 mm
------------	-------------------