

Switch 4xPOE + 1xUplink 4-Port PoE Switch (Unmanaged)



Product Overview

The Switch is a layer two fast ethernet switch, which supports 250 meters long distance PoE transmission. It provides 4*10/100Mbps PoE ports and 1*100 Mbps uplink ports. In order to acquire smooth monitoring, it's recommended to connect max 4 IP cameras at a bit rate of less than 4Mbps respectively.

Technical Specification

Ethernet Port	1*10/100 Base-T 4*10/100 Base-T (PoE power supply)
PoE Power Consumption	Port1≤60W, Port2-4≤30W, Totals60W
PoE PIN Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
PoE Power Management	Support
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	1Gbps
Packet Forwarding Rate	744Kpps
Packet Buffer Memory	448Kb
MAC Table Size	1K
Flow Control	Enable
Application Humidity	5%~95%
Power	DC48~57V power adapter
Lightning Protection	Common Mode 2KV Differential Mode 1KV
ESD Protection	Air Discharge 8KV Contact Discharge 6KV
Working Temperature	-10°C~55°C
Weight	290g
Dimension(W×D×H)	130mm×85mm×26mm

Features

- Layer two commercial switch
- Supports PoE power management
- Supports wall-mount installation
- Supports anti-theft lock hole
- Supports auto learning and aging, MAC address capacity is 1K
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- RJ45 port supports 10/100Mbps self-adaptation
- Supports 250 meters long distance PoE transmission
- Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply